



ROOFTEC[®] XCS 500 SO MUCH MORE THAN A ROOF PUMP!



BUILT IN USA
WITH GLOBALLY SOURCED MATERIALS

ALL-IN-ONE Soft Washing AND Pressure Washing to Clean:

- Asphalt Shingles
- Cedar Shakes
- Composite Decking
- Vinyl Siding
- Concrete
- Wood Decks
- Clay Tiles
- Brick
- Stucco
- Stone Masonry

AND virtually any other exterior substrate!

HIGH PRESSURE CLEANING

- Set up to 2500 PSI for concrete cleaning
- Set up to 1000 PSI for wood cleaning
- Able to use standard pressure washing tips, oscillating tip, or up to a 20" surface cleaner
- Use metering valves on machine to pre-treat and post-treat with cleaning solutions

LOW PRESSURE CLEANING

- Set to below 600 PSI for more delicate substrates (roofing, siding, etc.)
- Mix manifold injects both surfactants and high strength Sodium Hypochlorite
- Uses food-grade, stainless steel Suttner spray gun with j-rod
- Spray up to 35-40 ft for easy roof and siding cleaning from the ground

FEATURES

- 5.5 GPM, High Performance General Pump with Stainless steel heads and ceramic plungers for chemical injection
- Extremely reliable and quiet 14hp Kohler Engine able to run for 7 hours on a single tank of gas
- Adjust between 100 and 2500 psi quickly with a pressure regulator
- Adjust SH easily between 0 and 6% and meter surfactant flow from 0 to 10 GPH

SPECIFICATIONS

ENGINE SPEED	2500 RPM (MAX) / 900 RPM (IDLE)
WATER PUMP RPM	1785 RPM (MAX)
WATER PUMP FLOW RATE	5.5 GPM (MAX)
BLEACH TANK CAPACITY	110 GALLONS
UTILITY TANKS CAPACITY	12 GALLONS (EACH)
CONSOLE WEIGHT	640 LBS. (DRY)
MAX OPERATING WEIGHT	1840 LBS. (FULL TANKS)
DIMENSIONS (HxDxW)	41 X 59 X 48 IN. 104.14 X 149.86 X 121.92 CM
INCLUDED SOLUTION HOSE	200FT. HIGH PRESSURE/CHEM RESISTANT HOSE
INCLUDED SUPPLY HOSE	100FT. STANDARD ½ GARDEN HOSE
INCLUDED ACCESSORIES	STAINLESS STEEL SPRAY GUN, J-ROD W/4 TIPS